



polymer(ic), 160 µm
- 4 Jahre/years

DCM Satin
Satin



IX1966
Satin Branco



IX1965
Satin Grafite



IX1964
Satin Cinza Glacial



IX1960
Rustic Grafite



polymer(ic), 140 µm & 160 µm
- 4 Jahre/years

DCM Savannah & Linen
Gold Savana & Telado



IX2019
Savana Preto
(DCM Savannah, 140 µm)



IX2020
Savana Escaravelho
(DCM Savannah, 140 µm)



IX1911
Brim Bege
(DCM Linen, 160 µm)



IX1912
Linho Cinza Glacial
(DCM Linen, 160 µm)



polymer(ic), 200 µm
- 4 Jahre/years

DCM Leather
Gold Couros



IX2016
Volpe Branco



IX2012
Volpe Borgonha



IX2014
Volpe Escaravelho



IX2015
Volpe Chocolate



IX2017
Volpe Preto



polymer(ic), 120 µm
- 8 Jahre/years

AMX Carbon Fiber
Gold Fibras



IX1955
Fibra 3D



IX1954
Fibra 4D



DCM SATIN™

Revision: 01 | Dated: 03/18/2021

Product:

DCM Satin™ is a line of products for decoration, with different colors, calendered polymeric PVC 160 µm (6.2 mil) , suitable for indoor and outdoor applications, with pressure sensitive repositionable adhesive and liner with 120 g/m² silicone paper, resistance to house cleaning products.

Physical Characteristics:

Characteristics	Test Method	Specifications
Dimensions (W x L)	Imprimax	1,22m x 25m (≈48-in x 27-yd)
Liner	Imprimax	120 g/m ²
Film Thickness	Imprimax	160 µm (6.2 mil)
Adhesion	NBR15394	Minimum 0,500 Kgf/mm
Release	NBR15394	Maximum 0,050 Kgf/mm
Tack	NBR15394	Minimum 0,500 Kgf/mm
Dimensional stability	Imprimax	≤ -3,0 %
Service Temperature (during installation)	Imprimax	-15°C a 70°C (5°F to 158 °F)
Flammability	NBR13434-3	Does not Propagate
Mold Resistance	Imprimax	Excellent

Face-stock and PVC caliper: Polymeric calendered PVC 160 µm (6.2 mil)

Note A: The opacity of the PVC face-stock may vary and must be considered when installed

Adhesive type: Repositionable Aqueous Acrylic sensible to pressure (non-toxic)

Liner: Silicone coated paper 120 g/m²


Analysis and application conditions: Three bodies of evidence, standard size in conformity of NBR15394

Temperature of 23°C (73°F) ± 2° with 50% ± 5% of relative humidity.

Good for:

Visual communication; environments decorations; walls coatings; ceilings; doors; home appliances; furniture; indoor and outdoor vessel decoration; vehicle panel details, facades; wall stickers; and more.

Recommendations:



Apply it on a smooth and flat surfaces previously cleaned by using isopropyl alcohol, avoiding contact with impurities, oiliness, grease, dust or any kind of chemical products that may inhibit the adhesion of the self-adhesive;

Install immediately after the liner removal and press the material against the substrate using the squeegee to a better performance of the self-adhesive;

After applied, avoid aggressive products and constant grip;

We indicate the removal of the material in a 90° angle, in a place free of sunlight and previously climate-controlled.

Resistance:

Water: Excellent adhesive resistance

Oil: Excellent

Isopropyl alcohol: Excellent

Acetic Acid 5%: Excellent

Never use: Petrol derived products, heavy solvents and corrosive agents

UV light: The material shows high UV Light resistance

Methodology: ASTM G155:2007 (CYCLE 8) - Operating Xenon Arc Light Apparatus for Exposure of Non-Metallic Materials

Note: Results obtained after 1500 hours exposed, proving the film does not suffer alterations on surface aspect and considering high UV light resistance, since it does not have development of the autocatalytic photo degradation process.

Ideal conditions to storage:

This product duo date is 12 months if not processed, packaged in original package and stocked in environments with temperature 30°C (86°F) maximum, with relative humidity in 70% maximum.

Durability expectations:

In horizontal applications, the durability expectation can be reduced by approximately 20%; depending on the technique applied in the installation and its conservation, this expectation may decrease or even extend; Perform pre-application tests to analyze the removal performance and adhesion on the desired surface.

Durability expectations (by color option) under normal conditions:

DCM Satin	Code	Vertical Exposure - Indoor durability up to	Vertical Exposure - Outdoor durability up to
White	SA9012	8 years	4 years
Graphite	SA8052		
Glacial Gray	SA8172		
Taupe Beige	SA7042		
Scarab	SA7022		
Antique Copper	SA7032		
Allure Blue	SA1082		

Note:

These expectations of durability are applied for products listed in this data sheet. All of declarations, technical information (including product physical characteristics and chemical resistance) and recommendations about these Imprimax films are reasoned in previous test, which presumably to be trustful, but do not constitute in a warranty. All Imprimax self-adhesive films are traded under the premise that the buyer declares, and agree, to be responsible for adopt/convert these materials, having independently defined the adaptation of the product for your intentions and your clients. The Imprimax self-adhesive film has durability against raw materials defect and production for one year after manufacturing date. When the product applied as indicated, the durability expectation is the same informed as the respective data sheet of the material in question. In case of confirmation of failure on storage or product application, the warranty is cancelled. It's expressly provided, and comprehended, that the only obligation from Imprimax is remedy exclusively to the buyer, under the warranty (and if any warranty expressed or implicit), to the replacement of the defective, without costs, at Imprimax installations or at the film place (to be defined for Imprimax) or, on the assumption that the restoration or replacement of the product don't be commercially possible, the compensation applies till the maximum value of the product used, considering it's imperfection, to that specified Imprimax criterion, line with the follow: The Warranty is explicitly appointed above replace any other expressed or implicit warranty, covering, but not limited to any implicit commercialization warranty, suitability to any specific use or violation. The buyer particularly disclaims and is excluded from every other warranties. No abdication, alteration, inclusion or modification of the conditions described before will be validated in case of not in definition in writing and properly signed manually by an Imprimax representative. The Imprimax compromise for defective film do not overtake the purchase value payed for the buyer and in any occurrence the Imprimax will held responsible for any incidental damage or caused by unforeseeable or not, causing by defects in these films freely of theses damages happen or are detected before the replacement or compensation of credits, originally or not by negligence. All the sales and respective contracts of the adhesive films are subject to acceptance for the buyer of the terms and conditions of this warranty. The Imprimax decline any term contained in any request of purchase and communications of any kind of buyer that become to disharmonize, disagree or additional to the present deal.

Important: there may be color variation between lots





DCM SAVANNAH™

Revision: 01 | Dated: 03/18/2021

Product:

DCM Savannah™ is a line of products for decoration, with different colors, calendered polymeric PVC 140 µm (5.5 mil), suitable for indoor and outdoor applications, with pressure sensitive permanent adhesive and liner with 120 g/m² silicone paper, resistance to house cleaning products.

Physical Characteristics:

Characteristics	Test Method	Specifications
Dimensions (W x L)	Imprimax	1,22m x 25m (≈48-in x 27-yd)
Liner	Imprimax	120 g/m ²
Film Thickness	Imprimax	140 µm (5.5 mil)
Adhesion	NBR15394	Minimum 0,500 Kgf/mm
Release	NBR15394	Maximum 0,050 Kgf/mm
Tack	NBR15394	Minimum 0,500 Kgf/mm
Dimensional stability	Imprimax	≤ -3,0 %
Service Temperature (during installation)	Imprimax	-15°C a 70°C (5°F to 158 °F)
Flammability	NBR13434-3	Does not Propagate
Mold Resistance	Imprimax	Excellent

Face-stock and PVC caliper: Polymeric calendered PVC 140 µm (5.5 mil)

Note A: The opacity of the PVC face-stock may vary and must be considered when installed

Adhesive type: Repositionable Aqueous Acrylic sensible to pressure (non-toxic)

Liner: Silicone coated paper 120 g/m²


Analysis and application conditions: Three bodies of evidence, standard size in conformity of NBR15394

Temperature of 23°C (73°F) ± 2° with 50% ± 5% of relative humidity.

Good for:

Visual communication; environments decorations; walls coatings; ceilings; doors; home appliances; furniture; indoor and outdoor vessel decoration; vehicle panel details, facades; wall stickers; and more.

Recommendations:



Apply it on a smooth and flat surfaces previously cleaned by using isopropyl alcohol, avoiding contact with impurities, oiliness, grease, dust or any kind of chemical products that may inhibit the adhesion of the self-adhesive;

Install immediately after the liner removal and press the material against the substrate using the squeegee to a better performance of the self-adhesive;

After applied, avoid aggressive products and constant grip;

We indicate the removal of the material in a 90° angle, in a place free of sunlight and previously climate-controlled.

Resistance:

Water: Excellent adhesive resistance

Oil: Excellent

Isopropyl alcohol: Excellent

Acetic Acid 5%: Excellent

Never use: Petrol derived products, heavy solvents and corrosive agents

UV light: The material shows high UV Light resistance

Methodology: ASTM G155:2007 (CYCLE 8) - Operating Xenon Arc Light Apparatus for Exposure of Non-Metallic Materials

Note: Results obtained after 1500 hours exposed, proving the film does not suffer alterations on surface aspect and considering high UV light resistance, since it does not have development of the autocatalytic photo degradation process.

Ideal conditions to storage:

This product duo date is 12 months if not processed, packaged in original package and stocked in environments with temperature 30°C (86°F) maximum, with relative humidity in 70% maximum.

Durability expectations:

In horizontal applications, the durability expectation can be reduced by approximately 20%; depending on the technique applied in the installation and its conservation, this expectation may decrease or even extend; Perform pre-application tests to analyze the removal performance and adhesion on the desired surface.

Durability expectations (by color option) under normal conditions:

Solid Colors	Code	Vertical Exposure - Indoor durability up to	Vertical Exposure - Outdoor durability up to
White	SV9012	8 years	4 years
Black	SV0012		
Glacial Gray	SV8172		
Taupe Beige	SV7042		
Cores Metálicas e Perolizadas	Code	Vertical Exposure - Indoor durability up to	Vertical Exposure - Outdoor durability up to
Scarab	SV7022	8 years	4 years
Antique Copper	SV7032		
Beryl	SV2142		
Allure Blue	SV1082		

Note:

These expectations of durability are applied for products listed in this data sheet. All of declarations, technical information (including product physical characteristics and chemical resistance) and recommendations about these Imprimax films are reasoned in previous test, which presumably to be trustful, but do not constitute in a warranty. All Imprimax self-adhesive films are traded under the premise that the buyer declares, and agree, to be responsible for adopt/convert these materials, having independently defined the adaptation of the product for your intentions and your clients. The Imprimax self-adhesive film has durability against raw materials defect and production for one year after manufacturing date. When the product applied as indicated, the durability expectation is the same informed as the respective data sheet of the material in question. In case of confirmation of failure on storage or product application, the warranty is cancelled. It's expressly provided, and comprehended, that the only obligation from Imprimax is remedy exclusively to the buyer, under the warranty (and if any warranty expressed or implicit), to the replacement of the defective, without costs, at Imprimax installations or at the film place (to be defined for Imprimax) or, on the assumption that the restoration or replacement of the product don't be commercially possible, the compensation applies till the maximum value of the product used, considering it's imperfection, to that specified Imprimax criterion, line with the follow: The Warranty is explicitly appointed above replace any other expressed or implicit warranty, covering, but not limited to any implicit commercialization warranty, suitability to any specific use or violation. The buyer particularly disclaims and is excluded from every other warranties. No abdication, alteration, inclusion or modification of the conditions described before will be validated in case of not in definition in writing and properly signed manually by an Imprimax representative. The Imprimax compromise for defective film do not overtake the purchase value payed for the buyer and in any occurrence the Imprimax will held responsible for any incidental damage or caused by unforeseeable or not, causing by defects in these films freely of theses damages happen or are detected before the replacement or compensation of credits, originally or not by negligence. All the sales and respective contracts of the adhesive films are subject to acceptance for the buyer of the terms and conditions of this warranty. The Imprimax decline any term contained in any request of purchase and communications of any kind of buyer that become to disharmonize, disagree or additional to the present deal.

Important: there may be color variation between lots





DCM LINEN™

Revision: 01 | Dated: 03/18/2021

Product:

DCM Linen™ is a line of products for decoration, with different colors, calendered polymeric PVC 160 µm (6.2 mil), suitable for indoor and outdoor applications, with pressure sensitive permanent adhesive and liner with 120 g/m² silicone paper, resistance to house cleaning products.

Physical Characteristics:

Characteristics	Test Method	Specifications
Dimensions (W x L)	Imprimax	1,22m x 25m (≈48-in x 27-yd)
Liner	Imprimax	120 g/m ²
Film Thickness	Imprimax	160 µm (6.2 mil)
Adhesion	NBR15394	Minimum 0,500 Kgf/mm
Release	NBR15394	Maximum 0,050 Kgf/mm
Tack	NBR15394	Minimum 0,500 Kgf/mm
Dimensional stability	Imprimax	≤ -3,0 %
Service Temperature (during installation)	Imprimax	-15°C a 70°C (5°F to 158 °F)
Flammability	NBR13434-3	Does not Propagate
Mold Resistance	Imprimax	Excellent

Face-stock and PVC caliper: Polymeric calendered PVC 160 µm (6.2 mil)

Note A: The opacity of the PVC face-stock may vary and must be considered when installed

Adhesive type: Repositionable Aqueous Acrylic sensible to pressure (non-toxic)

Liner: Silicone coated paper 120 g/m²


Analysis and application conditions: Three bodies of evidence, standard size in conformity of NBR15394

Temperature of 23°C (73°F) ± 2° with 50% ± 5% of relative humidity.

Good for:

Visual communication; environments decorations; walls coatings; ceilings; doors; home appliances; furniture; indoor and outdoor vessel decoration; vehicle panel details, facades; wall stickers; and more.

Recommendations:



Apply it on a smooth and flat surfaces previously cleaned by using isopropyl alcohol, avoiding contact with impurities, oiliness, grease, dust or any kind of chemical products that may inhibit the adhesion of the self-adhesive;

Install immediately after the liner removal and press the material against the substrate using the squeegee to a better performance of the self-adhesive;

After applied, avoid aggressive products and constant grip;

We indicate the removal of the material in a 90° angle, in a place free of sunlight and previously climate-controlled.

Resistance:

Water: Excellent adhesive resistance

Oil: Excellent

Isopropyl alcohol: Excellent

Acetic Acid 5%: Excellent

Never use: Petrol derived products, heavy solvents and corrosive agents

UV light: The material shows high UV Light resistance

Methodology: ASTM G155:2007 (CYCLE 8) - Operating Xenon Arc Light Apparatus for Exposure of Non-Metallic Materials

Note: Results obtained after 1500 hours exposed, proving the film does not suffer alterations on surface aspect and considering high UV light resistance, since it does not have development of the autocatalytic photo degradation process.

Ideal conditions to storage:

This product duo date is 12 months if not processed, packaged in original package and stocked in environments with temperature 30°C (86°F) maximum, with relative humidity in 70% maximum.

Durability expectations:

In horizontal applications, the durability expectation can be reduced by approximately 20%; depending on the technique applied in the installation and its conservation, this expectation may decrease or even extend; Perform pre-application tests to analyze the removal performance and adhesion on the desired surface.

Durability expectations (by color option) under normal conditions:

Solid Colors	Code	Vertical Exposure - Indoor durability up to	Vertical Exposure - Outdoor durability up to
Black	LN0012	8 years	4 years
White	LN9012		
Denim Beige	LN4102		
Denim Gray	LN8182		
Black Linen	LN0022		
Glacial Gray Linen	LN8192		
Taupe Beige Linen	LN7042		
Pearled and Metallic colors	Code	Vertical Exposure - Indoor durability up to	Vertical Exposure - Outdoor durability up to
Scarab Linen	LN7242	8 years	4 years
Antique Copper Linen	LN7212		
Allure Blue Linen	LN1122		

Note:

These expectations of durability are applied for products listed in this data sheet. All of declarations, technical information (including product physical characteristics and chemical resistance) and recommendations about these Imprimax films are reasoned in previous test, which presumably to be trustful, but do not constitute in a warranty. All Imprimax self-adhesive films are traded under the premise that the buyer declares, and agree, to be responsible for adopt/convert these materials, having independently defined the adaptation of the product for your intentions and your clients. The Imprimax self-adhesive film has durability against raw materials defect and production for one year after manufacturing date. When the product applied as indicated, the durability expectation is the same informed as the respective data sheet of the material in question. In case of confirmation of failure on storage or product application, the warranty is cancelled. It's expressly provided, and comprehended, that the only obligation from Imprimax is remedy exclusively to the buyer, under the warranty (and if any warranty expressed or implicit), to the replacement of the defective, without costs, at Imprimax installations or at the film place (to be defined for Imprimax) or, on the assumption that the restoration or replacement of the product don't be commercially possible, the compensation applies till the maximum value of the product used, considering it's imperfection, to that specified Imprimax criterion, line with the follow: The Warranty is explicitly appointed above replace any other expressed or implicit warranty, covering, but not limited to any implicit commercialization warranty, suitability to any specific use or violation. The buyer particularly disclaims and is excluded from every other warranties. No abdication, alteration, inclusion or modification of the conditions described before will be validated in case of not in definition in writing and properly signed manually by an Imprimax representative. The Imprimax compromise for defective film do not overtake the purchase value payed for the buyer and in any occurrence the Imprimax will held responsible for any incidental damage or caused by unforeseeable or not, causing by defects in these films freely of theses damages happen or are detected before the replacement or compensation of credits, originally or not by negligence. All the sales and respective contracts of the adhesive films are subject to acceptance for the buyer of the terms and conditions of this warranty. The Imprimax decline any term contained in any request of purchase and communications of any kind of buyer that become to disharmonize, disagree or additional to the present deal.

Important: there may be color variation between lots





DCM LEATHER™

Revision: 01 | Dated: 03/18/2021

Product:

DCM Leather™ is a line of products for decoration, with different colors, calendered polymeric PVC 200 µm (7.8 mil), suitable for indoor and outdoor applications, with pressure sensitive permanent adhesive and liner with 120 g/m² silicone paper, resistance to house cleaning products.

Physical Characteristics:

Characteristics	Test Method	Specifications
Dimensions (W x L)	Imprimax	1,22m x 25m (≈48-in x 27-yd)
Liner	Imprimax	120 g/m ²
Film Thickness	Imprimax	200 µm (7.8 mil)
Adhesion	NBR15394	Minimum 0,500 Kgf/mm
Release	NBR15394	Maximum 0,050 Kgf/mm
Tack	NBR15394	Minimum 0,500 Kgf/mm
Dimensional stability	Imprimax	≤ -3,0 %
Service Temperature (during installation)	Imprimax	-15°C a 70°C (5°F to 158 °F)
Flammability	NBR13434-3	Does not Propagate
Mold Resistance	Imprimax	Excellent

Face-stock and PVC caliper: Polymeric calendered PVC 200 µm (7.8 mil)

Note A: The opacity of the PVC face-stock may vary and must be considered when installed

Adhesive type: Repositionable Aqueous Acrylic sensible to pressure (non-toxic)

Liner: Silicone coated paper 120 g/m²

Analysis and application conditions: Three bodies of evidence, standard size in conformity of NBR15394

Temperature of 23°C (73°F) ± 2° with 50% ± 5% of relative humidity.

Good for:

Visual communication; environments decorations; walls coatings; ceilings; doors; home appliances; furniture; indoor and outdoor vessel decoration; vehicle panel details, facades; wall stickers; and more.

Recommendations:

Apply it on a smooth and flat surfaces previously cleaned by using isopropyl alcohol, avoiding contact with impurities, oiliness, grease, dust or any kind of chemical products that my inhibit the adhesion of the self-adhesive;

Install immediately after the liner removal and press the material against the substrate using the squeegee to a better performance of the self-adhesive;

After applied, avoid aggressive products and constant grip;

We indicate the removal of the material in a 90° angle, in a place free of sunlight and previously climate-controlled.

Resistance:

Water: Excellent adhesive resistance

Oil: Excellent

Isopropyl alcohol: Excellent

Acetic Acid 5%: Excellent

Never use: Petrol derived products, heavy solvents and corrosive agents

UV light: The material shows high UV Light resistance

Methodology: ASTM G155:2007 (CYCLE 8) - Operating Xenon Arc Light Apparatus for Exposure of Non-Metallic Materials

Note: Results obtained after 1500 hours exposed, proving the film does not suffer alterations on surface aspect and considering high UV light resistance, since it does not have development of the autocatalytic photo degradation process.

Ideal conditions to storage:

This product duo date is 12 months if not processed, packaged in original package and stocked in environments with temperature 30°C (86°F) maximum, with relative humidity in 70% maximum.

Durability expectations:

In horizontal applications, the durability expectation can be reduced by approximately 20%; depending on the technique applied in the installation and its conservation, this expectation may decrease or even extend; Perform pre-application tests to analyze the removal performance and adhesion on the desired surface.

Durability expectations (by color option) under normal conditions:

Solid Colors	Code	Vertical Exposure - Indoor durability up to	Vertical Exposure - Outdoor durability up to
Black	LT0012	8 years	4 years
Chocolate	LT7012		
Burgundy	LT5112		

Note:

These expectations of durability are applied for products listed in this data sheet. All of declarations, technical information (including product physical characteristics and chemical resistance) and recommendations about these Imprimax films are reasoned in previous test, which presumably to be trustful, but do not constitute in a warranty. All Imprimax self-adhesive films are traded under the premise that the buyer declares, and agree, to be responsible for adopt/convert these materials, having independently defined the adaptation of the product for your intentions and your clients. The Imprimax self-adhesive film has durability against raw materials defect and production for one year after manufacturing date. When the product applied as indicated, the durability expectation is the same informed as the respective data sheet of the material in question. In case of confirmation of failure on storage or product application, the warranty is cancelled. It's expressly provided, and comprehended, that the only obligation from Imprimax is remedy exclusively to the buyer, under the warranty (and if any warranty expressed or implicit), to the replacement of the defective, without costs, at Imprimax installations or at the film place (to be defined for Imprimax) or, on the assumption that the restoration or replacement of the product don't be commercially possible, the compensation applies till the maximum value of the product used, considering it's imperfection, to that specified Imprimax criterion, line with the follow: The Warranty is explicitly appointed above replace any other expressed or implicit warranty, covering, but not limited to any implicit commercialization warranty, suitability to any specific use or violation. The buyer particularly disclaims and is excluded from every other warranties. No abdication, alteration, inclusion or modification of the conditions described before will be validated in case of not in definition in writing and properly signed manually by an Imprimax representative. The Imprimax compromise for defective film do not overtake the purchase value payed for the buyer and in any occurrence the Imprimax will held responsible for any incidental damage or caused by unforeseeable or not, causing by defects in these films freely of theses damages happen or are detected before the replacement or compensation of credits, originally or not by negligence. All the sales and respective contracts of the adhesive films are subject to acceptance for the buyer of the terms and conditions of this warranty. The Imprimax decline any term contained in any request of purchase and communications of any kind of buyer that become to disharmonize, disagree or additional to the present deal.

Important: there may be color variation between lots





AMX CARBON FIBER

Revision: 01 | Dated: 11/10/2023

Product:

Gold Fiber is a line of products for car wrap, visual communication or decoration, textured color that simulate carbon fiber, calendered polymeric PVC 4.8 mil (120 μm), suitable for indoor and outdoor applications, with pressure sensitive repositionable adhesive and liner with 120 g/m^2 silicone paper.

Physical Characteristics:

<i>Characteristics</i>	<i>Test Method</i>	<i>Specifications</i>
Dimensions (W x L)	Imprimax	\approx 55-in 27-yd (1,40m x 25m)
Liner	Imprimax	120 g/m^2
Film Thickness	Imprimax	4.8 mil (120 μm)
Adhesion	NBR15394	Minimum 0,500 Kgf/mm
Release	NBR15394	Maximum 0,050 Kgf/mm
Tack	NBR15394	Minimum 0,500 Kgf/mm
Dimensional stability	Imprimax	\leq -3,0 %
Service Temperature (during installation)	Imprimax	-15°C a 70°C (5°F to 158 °F)
Flammability	NBR13434-3	Self-Extinguishing
Mold Resistance	Imprimax	Excellent

Face-stock and PVC caliper: Polymeric calendered PVC 4.8 mil (120 μm).

Note A: *The opacity of the PVC face-stock may vary and must be considered when installed*

Adhesive type: Repositionable Aqueous Acrylic sensible to pressure (non-toxic)

Liner: Silicone coated paper 120 g/m^2

Analysis and application conditions: Three bodies of evidence, standard size in conformity of NBR15394

Temperature of 23°C (73°F) ± 2° with 50% ± 5% of relative humidity.

Good for:

Visual communication; fleet decoration (partial personalization or full vehicle wrap and covering; Wall personalization; vessels and Jetskis; aircrafts; environment decoration, wall stickers; and more.

Recommendations:

Apply it on a smooth and flat surfaces previously cleaned by using isopropyl alcohol, avoiding contact with impurities, oiliness, grease, dust or any kind of chemical products that may inhibit the adhesion of the self-adhesive;

Install immediately after the liner removal and press the material against the substrate using the squeegee to a better performance of the self-adhesive;

After applied, avoid aggressive products and constant grip;

We indicate the removal of the material in a 90° angle, in a place free of sunlight and previously climate-controlled.

Resistance:

Water: Excellent adhesive resistance

Oil: Excellent

Isopropyl alcohol: Excellent

Acetic Acid 5%: Excellent

Never use: Petrol derived products, heavy solvents and corrosive agents

UV light: The material shows high UV Light resistance

Methodology: ASTM G155:2007 (CYCLE 8) - Operating Xenon Arc Light Apparatus for Exposure of Non-Metallic Materials

Note D: Results obtained after 1500 hours exposed, proving the film does not suffer alterations on surface aspect and considering high UV light resistance, since it does not have development of the autocatalytic photo degradation process.

Ideal conditions to storage:

This product duo date is 24 months if not processed, packaged in original package and stocked in environments with temperature 30°C (86°F) maximum, with relative humidity in 70% maximum.

Important: As of May 2, 2023, Imprimax has made improvements to its manufacturing process, bringing about changes regarding the durability of the product in stock, from 12 months to 24 months, provided that following the ideal storage recommendations mentioned above.

Durability expectations:

In horizontal applications, the durability expectation can be reduced by approximately 20%; depending on the technique applied in the installation and its conservation, this expectation may decrease or even extend; Perform pre-application tests to analyze the removal performance and adhesion on the desired surface.

Durability expectations (by color option) under normal conditions:

Carbon Fiber	Code	Vertical Exposure - Indoor durability up to	Vertical Exposure - Outdoor durability up to
3D Black	CF00113D	8 years	8 years
4D Black	PG00114D	8 years	8 years

Note:

These expectations of durability are applied for products listed in this data sheet. All of declarations, technical information (including product physical characteristics and chemical resistance) and recommendations about these Imprimax films are reasoned in previous test, which presumably to be trustful, but do not constitute in a warranty. All Imprimax self-adhesive films are traded under the premise that the buyer declares, and agree, to be responsible for adopt/convert these materials, having independently defined the adaptation of the product for your intentions and your clients. The Imprimax self-adhesive film has durability against raw materials defect and production for one year after manufacturing date. When the product applied as indicated, the durability expectation is the same informed as the respective data sheet of the material in question. In case of confirmation of failure on storage or product application, the warranty is cancelled. It's expressly provided, and comprehended, that the only obligation from Imprimax is remedy exclusively to the buyer, under the warranty (and if any warranty expressed or implicit), to the replacement of the defective, without costs, at Imprimax installations or at the film place (to be defined for Imprimax) or, on the assumption that the restoration or replacement of the product don't be commercially possible, the compensation applies till the maximum value of the product used, considering it's imperfection, to that specified Imprimax criterion, line with the follow: The Warranty is explicitly appointed above replace any other expressed or implicit warranty, covering, but not limited to any implicit commercialization warranty, suitability to any specific use or violation. The buyer particularly disclaims and is excluded from every other warranties. No abdication, alteration, inclusion or modification of the conditions described before will be validated in case of not in definition in writing and properly signed manually by an Imprimax representative. The Imprimax compromise for defective film do not overtake the purchase value paid for the buyer and in any occurrence the Imprimax will held responsible for any incidental damage or caused by unforeseeable or not, causing by defects in these films freely of theses damages happen or are detected before the replacement or compensation of credits, originally or not by negligence. All the sales and respective contracts of the adhesive films are subject to acceptance for the buyer of the terms and conditions of this warranty. The Imprimax decline any term contained in any request of purchase and communications of any kind of buyer that become to disharmonize, disagree or additional to the present deal.

Important: there may be color variation between lots